


# basic wire and cable

3900 N. ROCKWELL ST. CHICAGO, ILLINOIS 60618-3730, TEL: (773) 539-1800, FAX: (773) 539-3500

## BARE COPPER

Stranded  
Soft-Medium-Hard Drawn



Stranded Bare Copper

### APPLICATIONS:

Stranded (medium or hard-drawn temper) for use overhead outdoors on insulators for distribution circuits.  
Stranded (hard, medium or soft-drawn temper) for grounding.

### CONSTRUCTION:

Soft or annealed, bare concentric stranded copper conductor.

### STANDARDS:

1. Conforms to ASTM B-3 "Soft or Annealed Copper Wire."
2. Conforms to ASTM B-8 for "Concentric-Lay Stranded Copper Conductors."

| BASIC<br>CAT NO. | SIZE/<br>AWG.<br>KCMIL | NO. OF<br>STRDS. | O.D.<br>in. | WEIGHT<br>lbs/mft |
|------------------|------------------------|------------------|-------------|-------------------|
| 4-205            | 14                     | 7                | .073        | 12                |
| 4-206            | 12                     | 7                | .092        | 20                |
| 4-208            | 10                     | 7                | .116        | 32                |
| 4-210            | 8                      | 7                | .146        | 51                |
| 4-212            | 6                      | 7                | .184        | 81                |
| 4-214            | 4                      | 7                | .232        | 129               |
| 4-216            | 2                      | 7                | .292        | 205               |
| 4-217            | 1                      | 19               | .332        | 259               |
| 4-218            | 1/0                    | 19               | .373        | 326               |
| 4-219            | 2/0                    | 19               | .419        | 411               |
| 4-220            | 3/0                    | 19               | .470        | 518               |
| 4-221            | 4/0                    | 19               | .528        | 653               |
| 4-225            | 250                    | 37               | .575        | 772               |
| 4-226            | 300                    | 37               | .630        | 926               |
| 4-227            | 350                    | 37               | .681        | 1081              |
| 4-229            | 500                    | 37               | .813        | 1544              |
| 4-231            | 750                    | 61               | .998        | 2316              |

Dimensional data not binding. We reserve the right to alter specifications without notice.  
SHIPPING TOLERANCE +/- 10%